

SPEC SHEET

Edge of Dock Levelers

DL,NL,TS,HNL,HED Series Edge Of Dock Levelers



GENERAL DESCRIPTION: Poweramp® edge-of-dock levelers mount directly to the dock face and provide a recommended working range of +/-3" and a maximum operating range of +/-5" above or below dock. The units are offered with either mechanical or hydraulic operation. Poweramp® edge-of-dock levelers come in 5 series: DL, NL, TS, HNL, HED.

MECHANICAL: Mechanically-operated edge-of-dock levelers are the largest selling edge-of-dock levelers in the industry. Our dual extension spring lift mechanism offers proven efficiency and durability. Careful engineering and rugged construction ensure extended life. Operation is safe and easy. Includes the DL, NL, and TS series levelers.

HYDRAULIC: Hydraulically-operated edge-of-dock models offer the convenience and safety of push-button control. Poweramp's® hydraulic design, featuring power extension and retraction of the lip and deck and hydraulic lip lock, is the finest in the industry. Our exclusive speed

DIMENSIONS AND CAPACITIES CHARTS:

<u>DL Series Dimensions and Capacities</u>			
Model #	Deck Width	Total Unit Width	Comparative Industry Rating
DL-66	66"	104"	20,000
DL-72	72"	110"	25,000
DL-78	78"	116"	30,000 (N/A for DL-78)

<u>NL Series Dimensions and Capacities</u>			
Model #	Deck Width	Total Unit Width	Comparative Industry Rating
NL-66	66"	104"	20,000
NL-72	72"	110"	25,000
NL-78	78"	116"	30,000
NL-84	84'	122'	35,000 (N/A for NL-84)

Product Features



Lip Hinge Tubes Include Grease Fittings

Simple lubrication of hinge tubes provides ease of maintenance and longer life.



Maximum Operating Range

5' above dock and 5' below dock travel.



Never Lift Option

The never lift option provides the easiest mechanical EOD positioning available in the industry.

control adjusts leveler descent speed.
Includes the HNL and HED series levelers.

INSTALLATION: Unit shipped completely assembled and ready for installation.

WARRANTY: All EOD levelers come with Systems, Inc. standard product warranty. This includes (1) year from the date of shipment. The warranty covers repair or replacement of a defect as long as the product has been properly installed, maintained, and operated in accordance with all manufacturer's recommendations and/or specified design parameters and not otherwise have been subject to abuse, misuse, misapplication, acts of nature, overloading, unauthorized repair or modification, application in a corrosive environment or lack of maintenance.

DIMENSIONS AND CAPACITIES CHARTS (cont.):

<u>TS Series Dimensions and Capacities</u>			
Model #	Deck Width	Total Unit Width	Comparative Industry Rating
TS-66	66"	104"	20,000
TS-72	72"	110"	25,000
TS-78	78"	116"	30,000
TS-84	84'	122'	35,000 (N/A for TS-78 & 84)

<u>HNL Series Dimensions and Capacities</u>			
Model #	Deck Width	Total Unit Width	Comparative Industry Rating
HNL-66	66"	104"	20,000
HNL-72	72"	110"	25,000
HNL-78	78"	116"	30,000
HNL-84	84'	122'	35,000 (N/A for HNL-78 & 84)

<u>HED Series Dimensions and Capacities</u>			
Model #	Deck Width	Total Unit Width	Comparative Industry Rating
HED-66	66"	104"	20,000
HED-72	72"	110"	25,000
HED-78	78"	116"	30,000
HED-84	84'	122'	35,000

Product Features (cont.)



Hydraulic Option

Fully hydraulic operation available.
Simple push button design.



Milled Lip Option

Provides a smooth transition from the bed of the truck to the loading dock.



Safe and Easy Operation

The dual extension spring offers proven efficiency and durability.

BODE

MATERIAL HANDLING SOLUTIONS

www.bodedockanddoor.com

www.bodeequipment.com

800-797-5699